

Timer relay - ETD-BL-1T-ON-CC- 10S-PT - 2901480

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Timer relay with switch-on delay (with control contact) and an adjustable time range (0.1 s - 10 s), with push-in connection

The figure shows the ETD-BL-1T-ON-CC- 10S 2917418 version



Key commercial data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 60.0 GRM |
| Custom tariff number | 85364900 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|--------|--------|
| Width | 6.2 mm |
| Height | 80 mm |
| Depth | 86 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 65 °C |
| Ambient temperature (storage/transport) | -25 °C ... 80 °C |
| Permissible humidity (operation) | 15 % ... 85 % |
| Noise immunity | EN 61000-6-2 |

Coil side

| | |
|---------------------|--|
| Input voltage range | 24 V DC (19,2 V DC ...30 V DC) |
| Function | ON-CC: With switch-on delay with control contact |
| Time setting range | 0.1 s ... 10 s |

Contact side

Timer relay - ETD-BL-1T-ON-CC- 10S-PT - 2901480

Technical data

Contact side

| | |
|--------------|-------------------|
| Contact type | 1 floating PDT |
| Output fuse | 6.3 A (fast-blow) |

General

| | |
|----------------------------------|--|
| Status display | Green LED (POWER) |
| | Yellow LED (relay active) |
| Mechanical service life | Approx. 2×10^7 cycles |
| Mounting position | any |
| Assembly instructions | on standard DIN rail NS 35 in accordance with EN 60715 |
| Color | green |
| Housing insulation material | Polyamide PA, self-extinguishing |
| Permissible humidity (operation) | 15 % ... 85 % |
| Rated insulation voltage | 300 V AC (According to EN 50178) |
| Conformance | CE-compliant |
| ATEX | # II 3 G Ex nAC II T4 X |
| UL, USA / Canada | UL/C-UL listed UL 508 |

Connection data

| | |
|--|----------------------|
| Conductor cross section stranded min. | 0.14 mm ² |
| Conductor cross section stranded max. | 2.5 mm ² |
| Conductor cross section solid min. | 0.14 mm ² |
| Conductor cross section solid max. | 2.5 mm ² |
| Conductor cross section AWG/kcmil min. | 26 |
| Conductor cross section AWG/kcmil max | 14 |
| Stripping length | 8 mm |
| Connection method | Push-in connection |

Control contact

| | |
|----------------------|-------------------------------|
| Connection name | Non-floating, terminals A1-B1 |
| Control pulse length | min. 50 ms |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27371103 |
| eCl@ss 4.1 | 27371103 |
| eCl@ss 5.0 | 27371701 |
| eCl@ss 5.1 | 27371701 |
| eCl@ss 6.0 | 27371790 |

Timer relay - ETD-BL-1T-ON-CC- 10S-PT - 2901480

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 7.0 | 27371790 |
| eCl@ss 8.0 | 27371605 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001439 |
| ETIM 4.0 | EC001439 |
| ETIM 5.0 | EC001439 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211920 |
| UNSPSC 7.0901 | 39121519 |
| UNSPSC 11 | 39121519 |
| UNSPSC 12.01 | 39121519 |
| UNSPSC 13.2 | 39121519 |

Approvals

Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

ATEX

Approvals submitted

Approval details

| |
|---|
| UL Listed  |
|---|

| |
|--|
| cUL Listed  |
|--|

Timer relay - ETD-BL-1T-ON-CC- 10S-PT - 2901480

Approvals

cULus Listed 

Drawings

Block diagram

