

Surge protection device - CN-LAMBDA/4-5.9-BB - 2838490

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Attachment plug with Lambda/4 technology as surge protection for coaxial signal interfaces. Connection: N connectors socket-socket

Product Features

- High HF power in the kW range
- Outdoor surge protection
- As an adapter between devices and cables
- Maintenance-free surge protection with LAMBDA/4 technology
- Low protection level



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	140.19 GRM
Custom tariff number	85363010
Country of origin	United States

Technical data

Dimensions

Height	38 mm
Width	26.1 mm
Depth	60 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 90 °C
Degree of protection	IP68

General

Housing material	Brass (CuZn)
Color	nickel

Surge protection device - CN-LAMBDA/4-5.9-BB - 2838490

Technical data

General

Mounting type	Connection-specific intermediate plugging
Type	Attachment plug
Number of positions	1
Direction of action	Line-Shield/Earth Ground

Protective circuit

IEC test classification	C2
	C3
	D1
VDE requirement class	C2
	C3
	D1
Nominal current I_N	5 A (25 °C)
Nominal discharge current I_n (8/20) μ s (Core-Earth)	50 kA
Nominal discharge current I_n (8/20) μ s (Core-Shield)	50 kA
Total surge current (8/20) μ s	60 kA
Total surge current (10/350) μ s	20 kA
Max. discharge current I_{max} (8/20) μ s maximum (Core-Earth)	60 kA
Max. discharge current I_{max} (8/20) μ s maximum (Core-Shield)	60 kA
Impulse discharge current (10/350) μ s, peak value I_{imp}	≤ 20 kA
Output voltage limitation at 1 kV/ μ s (Core-Earth) spike	≤ 11 V (6 kV/3 kA)
Output voltage limitation at 1 kV/ μ s (Core-Shield) spike	≤ 11 V (6 kV/3 kA)
Output voltage limitation at 1 kV/ μ s (Core-Earth) static	≤ 11 V (6 kV/3 kA)
Output voltage limitation at 1 kV/ μ s (Core-Shield) static	≤ 11 V (6 kV/3 kA)
Voltage protection level U_p (Core-Earth)	≤ 11 V (6 kV/3 kA)
Voltage protection level U_p (Core-Shield)	≤ 11 V (6 kV/3 kA)
Input attenuation aE, asym.	typ. 0.05 dB (≤ 0.15 dB)
Frequency range	2.4 GHz ... 5.9 GHz
Standing wave ratio SWR in a 50 Ω system	typ. 1.1 (≤ 1.20 (2.4 GHz...5.9 GHz))
Permissible HF power P_{max} at VSWR = xx (50 ohm system)	≤ 500 W
	≤ 4 kW (peak)
Surge current resistance (conductor-ground)	C2 - 10 kV/5 kA
	D1 - 2,5 kA
Surge current resistance (conductor-shield)	C2 (10 kV/5 kA)
	D1 (2.5 kA)

Connection data

Connection method	N Connector
-------------------	-------------

Surge protection device - CN-LAMBDA/4-5.9-BB - 2838490

Technical data

Connection data

Connection type IN	N connector, female
Connection type OUT	N connector, female

Standards and Regulations

Standards/regulations	IEC 61643-21
-----------------------	--------------

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807

ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

GOST

Surge protection device - CN-LAMBDA/4-5.9-BB - 2838490

Approvals

Ex Approvals

Approvals submitted

Approval details

GOST 

Accessories

Accessories

Assembly adapter

Mounting plate - CN-UB/MP - 2818135



Tongue for attaching the CN-UB..., to housing panels, for example.

Mounting plate - CN-UB/MP-90DEG-50 - 2803137




Angled bracket for individually fixing CN-UB... to housing panels, for example.

Drawings

Surge protection device - CN-LAMBDA/4-5.9-BB - 2838490

Dimensioned drawing



Circuit diagram

