

## Ring cable lug - C-RCI 2,5/M3 - 3240021

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Ring cable lug, blue, 1.5-2.5 mm<sup>2</sup>, M3

### Why buy this product

- The insulated ring cable lugs with plastic sleeve are hard-soldered and feature the 'EASY ENTRY' system
- The sleeves are conically tapered to facilitate easy and correct insertion of the conductor
- 



### Key commercial data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 100 pc  |
| Minimum order quantity               | 100 pc  |
| GTIN                                 | <br>4 046356 451987 |
| Weight per Piece (excluding packing) | 0.8 g   |
| Custom tariff number                 | 85369010  |
| Country of origin                    | China   |

### Technical data

#### Dimensions

|   |         |
|---|---------|
| Length (b)  | 20.6 mm |
| Width (a)   | 6.6 mm  |
| Length of insulation sleeve (c)                           | 11 mm   |
| Inner dimension of the insulating collar (d)              | 4.5 mm  |
| Distance between the center and the insulation sleeve (e) | 7.8 mm  |
| Inner diameter (f)  | 3.2 mm  |
| Material thickness (g)                                    | 0.8 mm  |

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -20 °C ... 105 °C |
|---------------------------------|-------------------|

#### General

|       |      |
|-------|------|
| Color | blue |
|-------|------|

# Ring cable lug - C-RCI 2,5/M3 - 3240021

## Technical data

### General

|   |              |
|---|--------------|
| Stripping length                        | 8 mm         |
| Components                              | Halogen-free |
| Inflammability class according to UL 94 | V2           |
| Material                                | Copper       |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060701 |
| eCl@ss 4.1 | 27060701 |
| eCl@ss 5.0 | 27400201 |
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 7.0 | 27400201 |
| eCl@ss 8.0 | 27400204 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000005 |
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC001052 |
| ETIM 5.0 | EC001052 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 27113201 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11     | 27121703 |
| UNSPSC 12.01  | 27121703 |
| UNSPSC 13.2   | 27121703 |

## Approvals

### Approvals

---

Approvals

EAC / EAC

---

Ex Approvals

---

Approvals submitted

## Ring cable lug - C-RCI 2,5/M3 - 3240021

### Approvals

---

#### Approval details

EAC

EAC

### Drawings

Dimensional drawing

