

Connector - C-SCFFI 1,5/6,3X0,8 - 3240538

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Slip-on sleeve, fully isolated, red, 0.5 - 1.5 mm², for plug 6.3 x 0.8 mm

Why buy this product

- Hard-soldered crimping zone for maximum conductor pull-out forces in connection with CRIMPFOX RCI... pliers
- Easy and reliable conductor entry thanks to 'EASY ENTRY'
- Halogen-free
- Electrolytically tin-plated
-



Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| GTIN |  4 046356 528085 |
| Weight per Piece (excluding packing) | 1.23 g |
| Custom tariff number | 85369010 |
| Country of origin | China |

Technical data

Dimensions

| | |
|--|---------|
| Length (b) | 21.5 mm |
| Width (a) | 6.3 mm |
| Length of insulation sleeve (c) | 10.5 mm |
| Inner dimension of the insulating collar (d) | 4.3 mm |
| Material thickness (g) | 0.4 mm |

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -20 °C ... 105 °C |
| Short-term temperature | 120 °C |
| Max. permanent temperature | 105 °C |

Connector - C-SCFFI 1,5/6,3X0,8 - 3240538

Technical data

General

| | |
|------------------|--------------|
| Color | red |
| Stripping length | 7 mm |
| Components | Halogen-free |
| Material | Brass |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140815 |
| eCl@ss 4.1 | 27140815 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27400209 |
| eCl@ss 7.0 | 27440304 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000516 |
| ETIM 3.0 | EC000516 |
| ETIM 4.0 | EC000516 |
| ETIM 5.0 | EC000516 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211923 |
| UNSPSC 7.0901 | 39121522 |
| UNSPSC 11 | 39121522 |
| UNSPSC 12.01 | 39121522 |
| UNSPSC 13.2 | 39121522 |

Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

Approvals submitted

Connector - C-SCFFI 1,5/6,3X0,8 - 3240538

Approvals

Approval details

EAC

EAC

Drawings

Dimensional drawing

