

Connector - C-JCI 2,5 - 3240062

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Butt connector, fully isolated, blue, 1.5 - 2.5 mm²,

Why buy this product

- Hard-soldered crimping zone for maximum conductor pull-out force in connection with CRIMPFOX RCI... pliers
- Electrogalvanized
- Halogen-free
- Conductor protection against pushing through
-



Key commercial data

Packing unit	50 pc
Minimum order quantity	50 pc
GTIN	 4 046356 452809
Weight per Piece (excluding packing)	1.39 g
Custom tariff number	85369010
Country of origin	China

Technical data

Dimensions

Length (b)	25.3 mm
Inner dimension of the insulating collar (d)	4.5 mm
Material thickness (g)	0.8 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 105 °C
Short-term temperature	120 °C
Max. permanent temperature	105 °C

General

Color	blue
-------	------

Connector - C-JCI 2,5 - 3240062

Technical data

General

Stripping length	8 mm
Components	Halogen-free
Inflammability class according to UL 94	V2
Material	CU

Classifications

eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201

ETIM

ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC001052
ETIM 5.0	EC001052

UNSPSC

UNSPSC 6.01	27113201
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703

Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

Approvals submitted

Connector - C-JCI 2,5 - 3240062

Approvals

Approval details

EAC

EAC

Drawings

Dimensional drawing

