

## DIN rail perforated - NS 35/15 PERF (18X5,2) 2000MM - 1210006

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



NS 35 DIN rail, according to customer specifications, height: 15 mm, width: 35 mm

The illustration shows a version of the product



### Key Commercial Data

Packing unit	1 M
Minimum order quantity	5 M
Custom tariff number	72166190
Country of origin	Germany

### Technical data

#### Dimensions

Height	15 mm
Length	2000 mm
Width	35 mm

#### General

Coating	Galvanized, passivated with a thick layer
Test standard	In acc. with EN 60715: 2001

#### Standards and Regulations

Test standard	In acc. with EN 60715: 2001
---------------	-----------------------------

### Classifications

#### eCl@ss

eCl@ss 4.0	27110804
------------	----------

## DIN rail perforated - NS 35/15 PERF (18X5,2) 2000MM - 1210006

### Classifications

#### eCl@ss

eCl@ss 4.1	27110804
eCl@ss 5.0	27141143
eCl@ss 5.1	27141143
eCl@ss 6.0	27400602
eCl@ss 7.0	27400602
eCl@ss 8.0	27400602

#### ETIM

ETIM 2.0	EC001285
ETIM 3.0	EC001285
ETIM 4.0	EC000212
ETIM 5.0	EC000212

#### UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708
UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121708