

D-SUB connector - VS-09-PROFIBUS-SC - 1654549

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



D-SUB connector, Degree of protection: IP67, Number of positions: 9, Material: PA, Connection method: Screw connection, Cable exit: Angled, with integrated termination resistor



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	94.0 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Ambient conditions

Degree of protection	IP67
----------------------	------

General data

Number of positions	9
Signal type/category	PROFIBUS
Overvoltage category	II
Degree of pollution	2

Standards and Regulations

Order No.	1654549
Product key	ABNJAA
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	27140816
------------	----------

D-SUB connector - VS-09-PROFIBUS-SC - 1654549

Classifications

eCl@ss

eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260705
eCl@ss 7.0	27440309
eCl@ss 8.0	27440302

ETIM

ETIM 2.0	EC001121
ETIM 3.0	EC001132
ETIM 4.0	EC002641
ETIM 5.0	EC001132

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

D-SUB connector - VS-09-PROFIBUS-SC - 1654549

Accessories

Accessories

Protective cover

D-SUB protective cover - VS-09-SD - 1887086

D-SUB protective cover, shell size 1, IP54 degree of protection, for panel mounting frame and sleeve housing VS-09-...



Drawings

Dimensional
drawing

D-
SUB
connector

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>