


Printed-circuit board connector - MCDNV 1,5/ 4-G1-3,5 P26THR R56 - 1715510

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 8 A, Number of positions: 4, Pitch: 3.5 mm, Color: black, Contact surface: Tin

Key Commercial Data

Packing unit	1
GTIN	 4 046356 103152
Custom tariff number	85366990

Technical data

Dimensions

Pitch	3.50 mm
Dimension a	10.5 mm
Constructional height	16 mm
Length of the solder pin	2.6 mm

General

Range of articles	MCDNV 1,5/...-G1-THR
Rated voltage (III/3)	160 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	8 A
Color	black
Number of positions	4

Standards and Regulations

Order No.	1715510
Product key	AAAEGB
Connection in acc. with standard	EN-VDE
	CUL

Classifications

eCl@ss

eCl@ss 4.0	272607xx
------------	----------

Printed-circuit board connector - MCDNV 1,5/ 4-G1-3,5 P26THR R56 - 1715510

Classifications

eCl@ss

eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC002637

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

VDE Gutachten mit Fertigungsüberwachung / EAC / cULus Recognized / IECCEB CB Scheme


Ex Approvals

Approvals submitted

Approval details


Printed-circuit board connector - MCDNV 1,5/ 4-G1-3,5 P26THR R56 - 1715510

Approvals

VDE Gutachten mit Fertigungsüberwachung 	
Nominal current IN	8 A
Nominal voltage UN	160 V

EAC

cULus Recognized		
	B	D
Nominal current IN	8 A	8 A
Nominal voltage UN	150 V	150 V

IECEE CB Scheme 	
Nominal current IN	8 A
Nominal voltage UN	160 V