


## D-SUB bus connector - SUBCON 15 HD/M-SH - 5604602

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



D-SUB connector, 15-pos, male connector, one cable entry < 35°, universal type for all systems, pin assignment: 1, 2, 3, ..., 14, 15 to screw connection terminal block

### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 685214
Weight per Piece (excluding packing)	75.5 g
Custom tariff number	85366990
Country of origin	United States

### Technical data

#### Dimensions

Max. cable diameter	12.7 mm
Min. cable diameter	4 mm
Width	16 mm
Height	49.8 mm
Length	61 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 75 °C
---------------------------------	------------------

#### General

Nominal voltage $U_N$	48 V AC/DC
Nominal current $I_N$	1 A
Signal	Point-to-point
Insertion/withdrawal cycles	> 50
SUBCON fixing screws	4-40 UNC
Tightening torque	0.4 Nm
Housing material	ABS, metal-plated
Pin assignment	All connections are 1:1 on the screw terminal block

#### Connection data

Connection	D-SUB connection
------------	------------------

## D-SUB bus connector - SUBCON 15 HD/M-SH - 5604602

### Technical data

#### Connection data

Number of positions	15
Connection method	High density D-SUB pin strip

### Classifications

#### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440302
eCl@ss 9.0	27440302

#### ETIM

ETIM 3.0	EC001132
ETIM 4.0	EC001132
ETIM 5.0	EC001132

#### UNSPSC

UNSPSC 6.01	30211802
UNSPSC 7.0901	39121402
UNSPSC 11	39121402
UNSPSC 12.01	39121402
UNSPSC 13.2	39121402