


# Printed-circuit board connector - CCV 2,5/ 4-GF-5,08 P26 AU THR - 1717071

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 12 A, Number of positions: 4, Pitch: 5.08 mm, Color: black, Contact surface: Gold, Mounting: THR soldering



## Key Commercial Data

Packing unit	1
GTIN	 4 046356 137515
Custom tariff number	85366990

## Technical data

### Dimensions

Length	8.6 mm
Pitch	5.08 mm
Dimension a	15.24 mm
Constructional height	13 mm
Height	12 mm
Length of the solder pin	2.6 mm
Pin dimensions	1 x 1 mm
Hole diameter	1.6 mm

### General

Range of articles	CCV 2,5/...-GF
Rated voltage (III/3)	250 V
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	12 A
Color	black
Number of positions	4

## Standards and Regulations

# Printed-circuit board connector - CCV 2,5/ 4-GF-5,08 P26 AU THR - 1717071

## Technical data

### Standards and Regulations

Connection in acc. with standard	EN-VDE
----------------------------------	--------

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC002637

### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Approvals

### Approvals

---

Approvals

EAC / EAC

---

Ex Approvals

---

# Printed-circuit board connector - CCV 2,5/ 4-GF-5,08 P26 AU THR - 1717071

## Approvals

Approvals submitted

---

### Approval details

EAC
-----

EAC
-----