

SC-RJ female insert - VS-SCRJ-GOF-BU/BU - 1652978

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



SC-RJ socket insert, duplex, for VS-A-F-IP67 panel mounting frame, can be used for fiberglass (multi-mode and single mode), PCF, and polymer fibers


Product Features

- Suitable for fiber types:
 - POF (980/1000 μm)
 - PCF (200/230 μm)
 - GOF MM (50/125 μm)
 - GOF SM (9/125 μm)



Ethernet

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 969943
Weight per Piece (excluding packing)	10.6 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Mechanical characteristics

Number of positions	2
Number of slots	1
Connection profile	SC-RJ, according to DIN EN 50377-6-1
Fiber type	GOF, PCF, POF
Fiber	POF, PCF, GOF
Ferrule diameter	2.50 mm
Number of fibers	2
Insertion/withdrawal cycles	≥ 500

SC-RJ female insert - VS-SCRJ-GOF-BU/BU - 1652978

Technical data

Mechanical characteristics

Connection method	Coupling
Color	black

Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C
Degree of protection	IP20

Material data

Flammability rating according to UL 94	V0
Housing material	PBT
Ferrule material	Zirconia ceramics
Ferrule holder color	white

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260705
eCl@ss 7.0	27440309
eCl@ss 8.0	19170122
eCl@ss 9.0	19170122

ETIM

ETIM 2.0	EC000764
ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC001122

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501

SC-RJ female insert - VS-SCRJ-GOF-BU/BU - 1652978

Classifications

UNSPSC

UNSPSC 13.2	31261501
-------------	----------

Approvals

Approvals

Approvals

EAC / EAC / EAC

Ex Approvals

Approvals submitted

Approval details

EAC

EAC

EAC

Drawings

Dimensional drawing

SC-
RJ
coupling
