



[Home](#) |
 [Products](#) |
 [PCB terminal blocks and PCB connectors](#) |
 [PCB connectors](#) |
 [Product list PCB connectors](#)

Printed-circuit board connector - DMC 1,5/ 2-G1F-3,5-LR P26THR - 1874014



Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 2, Pitch: 3.5 mm, Color: black, Contact surface: Tin, Mounting: THR soldering

This product is not yet available in the United States

The figure shows a 10-pos. version with 20 contacts

[Find a distributor](#)

[Add to wish list](#)

Overview

[Technical data](#)


[FAQs](#)

[Approvals](#)

[Downloads](#)

Your advantages

- Designed for integration into the SMT soldering process
- Screwable flange for superior mechanical stability
- Automatic locking and intuitive release through Lock and Release operating lever in contrasting color
- Conductor connection on several levels enables higher contact density
- Small component size for applications where space is at a premium



Key Commercial Data

Orderkey	1874014
Packing unit	1
GTIN	4055626259291
Custom tariff number	85366990

PHOENIX CONTACT

586 Fulling Mill Road
Middletown, PA 17057

(800) 888-7388

[▶ Contact us](#)

[▶ Your local sales contact](#)