

Fuse plug - P-FU 6,3X32 LED 60-EX - 3046512

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Fuse plug, Nominal current: 10 A, Width: 8.2 mm, Fuse type: G / 6,3 x 32, Fuse type: Glass / ceramics / ..., Color: black

Why buy this product

- ✓ Versions with bipolar defect indicator
- ▼ Test contacts on both sides of the fuse
- ☑ Can be used for overload/short-circuit protection



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	50 STK
Custom tariff number	85369085
Country of origin	Poland

Technical data

General

Note	Prior to replacing the cartridge fuse, disconnect the fuse connector from the basic terminal block.
Number of levels	1
Color	black
Insulating material	PA
Flammability rating according to UL 94	V0
Area of application	Machine building
	Plant engineering

Dimensions



Fuse plug - P-FU 6,3X32 LED 60-EX - 3046512

Technical data

Dimensions

Width	8.2 mm
Length	40 mm

General

Fuse	G / 6,3 x 32
Fuse type	Glass / ceramics /
Degree of pollution	3
Maximum power dissipation	1.6 W (Short-circuit and overload protection)
LED voltage range	30 V AC/DC 60 V AC/DC
LED current range	0.4 mA 0.86 mA
Maximum load current	10 A (the current is determined by the fuse used)
Nominal current I _N	10 A (the current is determined by the fuse used)
Open side panel	No

Standards and Regulations

Flammability rating according to UL 94	V0

Drawings

Circuit diagram



Application drawing

Fuse terminal blocks in interconne arrangement block consisting of 5 fuse terminal blocks

Application drawing

Fuse terminal block in single arrangement,



Fuse plug - P-FU 6,3X32 LED 60-EX - 3046512

block consisting of

one fuse

terminal

block

and

4

feedthrough

terminal

blocks

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27141149
eCl@ss 9.0	27141149

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000899
ETIM 5.0	EC002018

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com