

Filler plugs - HC-K-BS-M32-BK - 1410754

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Filler plug, plastic, size: M32

Filler plugs



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
Weight per Piece (excluding packing)	8.000 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Ambient conditions

Degree of protection	IP65
	IP65
	IP66 (Tightening torque 3.0 Nm)
Ambient temperature (operation)	-30 °C 100 °C

General

Type of the screw connection	M32
Material	Polyamide fiberglass reinforced
Seal material	CR
Thread type on connection side	M32
Torque	3 Nm
Flammability rating according to UL 94	НВ
Color	black



Filler plugs - HC-K-BS-M32-BK - 1410754


Technical data

General

	black
Standards and Regulations	
Flammability rating according to UL 94	НВ

Drawings

Dimensional drawing



Dimensional drawing

Classifications

eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	23111190
eCl@ss 9.0	23111190

ETIM

ETIM 4.0	EC000032
ETIM 5.0	EC000723

UNSPSC

UNSPSC 6.01	30211808
UNSPSC 7.0901	39121408
UNSPSC 11	39121408
UNSPSC 12.01	39121408



Filler plugs - HC-K-BS-M32-BK - 1410754

Classifications

UNSPSC

UNSPSC 13.2	39121408	
Approvals		
Approvals		
Approvals		
EAC		
Ex Approvals		
Approval details		
EAC 7500651.22.01.00246		

Phoenix Contact 2016 @ - all rights reserved http://www.phoenixcontact.com