

Cable gland - G-INS-PG13,5-S68N-NNES-S - 1411173


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Nickel-plated brass, External cable diameter 6 mm ... 12 mm, Shielding: No, Connecting thread: Pg13.5, Color: silver



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 STK |
| Minimum order quantity | 5 STK |
| GTIN |  4 046356 923071 |
| GTIN | 4046356923071 |
| Weight per Piece (excluding packing) | 32.000 g |
| Custom tariff number | 74199990 |
| Country of origin | Turkey |

Technical data

Dimensions

| | |
|---------------------------------|--------------------------------|
| Length | 30 mm |
| Wrench size, union nut | 22 mm |
| Wrench size, support | 22 mm |
| Hexagon angular dimension | 24.5 mm |
| Length of the connecting thread | 6.5 mm |
| Feed-through hole diameter | 20.5 mm ... 20.7 mm |
| External cable diameter | 6 mm ... 12 mm |
| | 10 mm ... 12 mm (for UL 514 B) |

Ambient conditions

| | |
|----------------------|------|
| Degree of protection | IP69 |
|----------------------|------|

Cable gland - G-INS-PG13,5-S68N-NNES-S - 1411173

Technical data

Ambient conditions


| | |
|---------------------------------|----------------------------|
| | IP68 (5 bar, 30 min.) |
| | 4X |
| Ambient temperature (operation) | -20 °C ... 100 °C (static) |

General

| | |
|--------------------------------|--|
| No. of conductors | 1 |
| Cable gland material | Nickel-plated brass |
| Material, insert | Polyamide 6 |
| Cable seal material | Neoprene |
| Shielded | No |
| Thread type on connection side | Pg13.5 |
| Torque | 5.5 Nm (Union nut) |
| | 5.5 Nm (Support) |
| | 8 Nm (for UL514 B: union nut / support) |
| Color | silver |
| Assembly instructions | 1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque |

Drawings

Dimensional drawing



Dimensional drawing

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Cable gland - G-INS-PG13,5-S68N-NNES-S - 1411173


Approvals

Ex Approvals

Approval details

UL Recognized <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> E199260

cUL Recognized <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> E199260

cULus Recognized  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>
