

Marker for terminal blocks from the SNK series from ABB - UCT6M-TM 6 - 0830757

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Marker for terminal blocks from the SNK series from ABB, Sheet, white, unlabeled, can be labeled with: THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Snap into tall marker groove, for terminal block width: 6 mm, Lettering field: 4.85 x 11.3 mm

Why buy this product

- UniCard marking for terminal blocks from other manufacturers (ABB) with flat marker groove
- The multi-section marking strips are easy to fit and can be easily separated if required



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
GTIN	4 046356 745635
GTIN	4046356745635
Weight per Piece (excluding packing)	12.000 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Dimensions

Length (b)	11.9 mm
Width (a)	5.45 mm
Height	2.7 mm

Ambient conditions

Ambient temperature (operation)	-40 °C 120 °C



Marker for terminal blocks from the SNK series from ABB - UCT6M-TM 6 - 0830757

Technical data

General

Note	Can be labeled via thermal transfer
Color	white
Components	free from silicone, halogen, and cadmium
Flammability rating according to UL 94	V0
Material	PC
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	50
Number of individual labels per row	10
RoHS compliant	Yes
Printability	Thermal transfer
	Inkjet printing
Device	5146464 THERMOMARK CARD
	5147888 BLUEMARK LED
	5147999 BLUEMARK CLED
Ink ribbon	0830808 THERMOMARK CARD-UCT-MAG23
	0801371 THERMOMARK-RIBBON 110-TC
	5147421 BLUEMARK FLUID-CARTRIDGE
	5146662 BLUEMARK CLED-FLUID-CARTR.
Test for substances that would hinder coating with paint or varnish	VW PV 3.10.7:2005-02
Result	Test passed
Test specification weathering-resistance	Following ISO 4892-2:2013-03
Test duration	96 h
Wipe resistance test result	Test passed
Salt spray test specification	DIN EN 60068-2-11:2000-02
Test duration	96 h
Salt spray testing result	Test passed
Alternating condensation climate with SO2 test specification	DIN 50018:2013-05
Climate level	AHT 1.0 S
Cycles	2
Condensation test result	Test passed
Wipe resistance of test specification inscriptions	DIN EN 61010-1 (VDE 0411-1):2011-07
Result	Test passed
Marking mounting type	Snap into tall marker groove

Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)



Marker for terminal blocks from the SNK series from ABB - UCT6M-TM 6 - 0830757

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com