

Protective covers - HC-B 6-SD-MLT/FS-AL - 1644546

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Protective cover B6, With single locking latch, Protective cover material: Al, Seal: yes, With lanyard, Diameter of retaining cord eyelet: 30 mm



RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 904876
GTIN	4017918904876
Weight per Piece (excluding packing)	73.760 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

Dimensions

Diameter of retaining cord eyelet	30 mm
-----------------------------------	-------

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

General

Size	B6
Type	For sleeve housing without single locking latch
Material	Aluminum, die-cast
Seal material	NBR
Locking latch material	High-grade steel, handle: PA-GF

Protective covers - HC-B 6-SD-MLT/FS-AL - 1644546

Technical data

General

Seal present	yes
Assembly instructions	Not for HC-B...EMC housings
Connection	The guide pins of the protective cover must be removed when using coding sockets, pins, and bolts.

Classifications

eCl@ss

eCl@ss 4.0	27141210
eCl@ss 4.1	27141210
eCl@ss 5.0	27149110
eCl@ss 5.1	27149110
eCl@ss 6.0	27261210
eCl@ss 7.0	27440208
eCl@ss 8.0	27440208
eCl@ss 9.0	27440208

ETIM

ETIM 2.0	EC000241
ETIM 3.0	EC002040
ETIM 4.0	EC002314
ETIM 5.0	EC002314
ETIM 6.0	EC002314

UNSPSC

UNSPSC 6.01	30212113
UNSPSC 7.0901	39121712
UNSPSC 11	39121712
UNSPSC 12.01	39121712
UNSPSC 13.2	39121421

Approvals

Approvals

Approvals

EAC

Protective covers - HC-B 6-SD-MLT/FS-AL - 1644546

Approvals

Ex Approvals

Approval details

EAC		7500651.22.01.00246
-----	---	---------------------