

## Housing - HC-STA-D07-BAWS-EL-AL - 1419252


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Panel mounting base D7, With single locking latch, Material: Die-cast aluminum, salt water resistant, Height: 28.5 mm, Cable gland: none, Gland: no, Standard, angled



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 159836
GTIN	4055626159836
Custom tariff number	85389099
Country of origin	China

### Technical data

#### Dimensions

Height	28.5 mm
Width	38 mm
Length	24.2 mm
Length of the assembly cutout	21.5 mm
Width of the assembly cutout	21.5 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP66
	IP67
Degree of protection of housing (NEMA)	4 (UL 50e)
	4X (UL 50e)

## Housing - HC-STA-D07-BAWS-EL-AL - 1419252

### Technical data

#### Ambient conditions

	12 (UL 50e)
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

Note	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05, Q07, Q12
Size	D7
Housing type	Panel mounting base
Locking type	With single locking latch
Screw connection	none
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	Uncoated

### Approvals

#### Approvals

---

#### Approvals


#### EAC

---

#### Ex Approvals

---

#### Approval details

EAC		EAC-Zulassung
-----	---	---------------