

## Housing - HC-STA-D07-HHFS-1TGM20-PL-BK - 1419255


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve housing D7, for single locking latch, Material: PA, Cable outlets: 1, straight, Height: 77.6 mm, Cable gland: with, Gland: no, 1x M20, Standard

RoHS

### Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 159966
GTIN	4055626159966
Weight per Piece (excluding packing)	20.000 g
Custom tariff number	85389099
Country of origin	China

### Technical data

#### Dimensions

Height	77.6 mm
Width	34.2 mm
Length	26.5 mm
Wrench size, union nut	22 mm
External cable diameter	4 mm ... 10 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP66
Degree of protection of housing (NEMA)	12 (UL 50e)
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

# Housing - HC-STA-D07-HHFS-1TGM20-PL-BK - 1419255

## Technical data

### General

Note	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05, Q07, Q12
Size	D7
Housing type	Sleeve housing
Color	black
Locking type	for single locking latch
Torque	Locking screw
No. of cable outlets	1
Cable exit	straight
Screw connection	with
Type of the screw connection	1x M20
Housing material	PA
Material lock	PA

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

### Approval details

EAC		EAC-Zulassung
-----	---	---------------

---