

## Housing - HC-STA-D07-SHOWS-1STM20-EL-AL - 1419253


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Box mounting bases D7, With single locking latch, Material: Die-cast aluminum, salt water resistant, Cable outlets: 1, lateral, Height: 27.9 mm, Cable gland: none, Gland: Yes, 1x M20, Standard, open floor



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 159843
GTIN	4055626159843
Custom tariff number	85389099
Country of origin	China

### Technical data

#### Dimensions

Height	27.9 mm
Width	38 mm
Length	24.2 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP66
	IP67
Degree of protection of housing (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Ambient temperature (operation)	-40 °C ... 125 °C

# Housing - HC-STA-D07-SHOWS-1STM20-EL-AL - 1419253

## Technical data

### General

Note	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05, Q07, Q12
Size	D7
Housing type	Box mounting bases
Locking type	With single locking latch
No. of cable outlets	1
Cable exit	lateral
Screw connection	none
Type of the screw connection	1x M20
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	Uncoated

## Approvals

### Approvals

---

Approvals


EAC

---

Ex Approvals

---

### Approval details

EAC		EAC-Zulassung
-----	---	---------------

---