

## Housing - HC-STA-D07-HHFS-1STP11-EL-AL - 1419237


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve housing D7, for single locking latch, Material: Die-cast aluminum, salt water resistant, Cable outlets: 1, lateral, Height: 52.8 mm, Cable gland: none, Gland: Yes, 1x Pg11, Standard

RoHS

### Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 159706
GTIN	4055626159706
Custom tariff number	85389099
Country of origin	China

### Technical data

#### Dimensions

Height	52.8 mm
Width	40.7 mm
Length	26.9 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP66
	IP67
Degree of protection of housing (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

# Housing - HC-STA-D07-HHFS-1STP11-EL-AL - 1419237

## Technical data

### General

Note	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05, Q07, Q12
Size	D7
Housing type	Sleeve housing
Locking type	for single locking latch
No. of cable outlets	1
Cable exit	lateral
Screw connection	none
Type of the screw connection	1x Pg11
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	Uncoated

## Approvals

### Approvals

---

Approvals


EAC

---

Ex Approvals

---

### Approval details

EAC		EAC-Zulassung
-----	---	---------------

---