

Protective covers - HC-STA-D07-HCLWS-PL-BK - 1419275


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Protective cover D7, With single locking latch, Material: PA, Protective cover material: PA, Height: 28 mm, Seal: no, Standard, With lanyard, Diameter of retaining cord eyelet: 25 mm, for pin inserts



Key Commercial Data

| | |
|----------------------|---|
| Packing unit | 1 STK |
| GTIN |  4 055626 160269 |
| GTIN | 4055626160269 |
| Custom tariff number | 85389099 |
| Country of origin | China |

Technical data

Dimensions

| | |
|--------|---------|
| Height | 28 mm |
| Width | 24.2 mm |
| Length | 24.2 mm |

Ambient conditions

| | |
|--------------------------------------|-------------------|
| Degree of protection of housing (IP) | IP66 |
| Ambient temperature (operation) | -20 °C ... 100 °C |

General

| | |
|--------------|---|
| Size | D7 |
| Type | For sleeve housing without single locking latch |
| Housing type | Protective cover |
| Color | black |

Protective covers - HC-STA-D07-HCLWS-PL-BK - 1419275

Technical data

General

| | |
|--|--|
| Locking type | With single locking latch |
| Housing material | PA |
| Material lock | PA |
| Material, protective cover | PA |
| Flammability rating according to UL 94 | V0 |
| Connection | Plastic protective cover for short-term protection |

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|---------------|
| EAC |  | EAC-Zulassung |
|-----|---|---------------|
