

Housing - HC-STA-D07-HHFS-1TGM25-PL-BK - 1419256


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve housing D7, for single locking latch, Material: PA, Cable outlets: 1, straight, Height: 81.8 mm, Cable gland: with, Gland: no, 1x M25, Standard

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 159973
GTIN	4055626159973
Weight per Piece (excluding packing)	40.000 g
Custom tariff number	85389099
Country of origin	China

Technical data

Dimensions

Height	81.8 mm
Width	34.2 mm
Length	26.5 mm
Wrench size, union nut	27 mm
External cable diameter	10 mm ... 16 mm

Ambient conditions

Degree of protection of housing (IP)	IP66
Degree of protection of housing (NEMA)	12 (UL 50e)
Ambient temperature (operation)	-40 °C ... 125 °C

General

Housing - HC-STA-D07-HHFS-1TGM25-PL-BK - 1419256

Technical data

General

Note	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05, Q07, Q12
Size	D7
Housing type	Sleeve housing
Color	black
Locking type	for single locking latch
Torque	Locking screw
No. of cable outlets	1
Cable exit	straight
Screw connection	with
Type of the screw connection	1x M25
Housing material	PA
Material lock	PA

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		EAC-Zulassung
-----	---	---------------