

RJ45 connector - CUC-INI-C1ZNI-S/R4IE8 - 1421608

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 connector, Degree of protection: IP20, Number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), Material: Zinc die-cast, Connection method: IDC fast connection, Connection cross section: AWG 26-24, Cable exit: straight

Why buy this product

- ✓ assembly without special tools
- ✓ One-Piece Design
- ✓ AWG 26-24
- ✓ 360° shielding
- ✓ High shock and vibration resistance



Ethernet

Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 276595
GTIN	4055626276595
Custom tariff number	85366990
Country of origin	Germany

Technical data

Mechanical characteristics

Number of positions	8
Connection profile	RJ45
Insertion/withdrawal cycles	≥ 750
Connection method	IDC fast connection
Conductor cross section	0.14 mm² ... 0.25 mm² (solid)
	0.14 mm² ... 0.25 mm² (stranded)

RJ45 connector - CUC-INI-C1ZNI-S/R4IE8 - 1421608

Technical data

Mechanical characteristics

Connection cross section AWG	26 ... 24 (solid)
	26 ... 24 (stranded)
Max. cable diameter	5 mm ... 9 mm
External cable diameter	5 mm ... 9 mm
Cable exit	straight
Wire diameter including insulation	≤ 1.6 mm
Degree of protection	IP20
Design	RJ45, IP20
No. of cable outlets	1

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
---------------------------------	------------------

Material data

Flammability rating according to UL 94	V0
Housing material	Zinc die-cast
Contact carrier material	PC
Contact material	Copper alloy
Contact surface material	Gold over nickel

Electrical characteristics

Number of positions	8
Transmission speed	1 Gbps
Transmission characteristics (category)	CAT5 (IEC 11801:2002)
GRP transmission properties	CAT5 (IEC 11801:2002)
Transmission speed	1 Gbps
Frequency range	to 100 MHz
Rated current	1.75 A
Overvoltage category	I
Contact resistance	0.001 Ω (Wire – IDC)
	0.005 Ω (Litz wires – IDC)
Rated voltage (III/3)	50 V

Standards and Regulations

Flammability rating according to UL 94	V0
--	----


Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

RJ45 connector - CUC-INI-C1ZNI-S/R4IE8 - 1421608

Drawings

Dimensional drawing



RJ45 connector, IP20

Approvals

Approvals

Approvals

cULus Recognized

Ex Approvals

Approval details

cULus Recognized		 http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm		E335024-20170228
Nominal current I _N		0.175 A		
Nominal voltage U _N		56.5 V		