

PCB terminal block - MKDSO 2,5/ 2-L BU - 2901505

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




PCB terminal block

Why buy this product

- PCB terminal block for ME/ME MAX electronics housing
- 5 mm pitch
- PCB terminal block orthogonal to the PCB



Key Commercial Data

Packing unit	50 STK
Minimum order quantity	200 STK
GTIN	 4 046356 143998
GTIN	4046356143998
Weight per Piece (excluding packing)	3.550 g
Custom tariff number	85369010
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

PCB terminal block - MKDSO 2,5/ 2-L BU - 2901505

Approvals


Approvals

CSA / VDE Gutachten mit Fertigungsüberwachung / CCA / IECEE CB Scheme / EAC / cULus Recognized


Ex Approvals

Approval details

CSA		http://www.csagroup.org/services/testing-and-certification/certified-product-listing/	13631
		B	D
mm ² /AWG/kcmil		28-12	28-12
Nominal current IN		10 A	10 A
Nominal voltage UN		300 V	300 V

VDE Gutachten mit Fertigungsüberwachung		http://www.vde.com/en/Institute/OnlineService/VDE-approved-products/Pages/Online-Search.aspx	40023968
mm ² /AWG/kcmil		0.2-2.5	
Nominal current IN		24 A	
Nominal voltage UN		450 V	


CCA			CCA/DE1 33724
mm ² /AWG/kcmil		2.5	
Nominal current IN		24 A	
Nominal voltage UN		450 V	

IECEE CB Scheme		http://www.iecee.org/	DE1-39126
mm ² /AWG/kcmil		2.5	
Nominal current IN		24 A	
Nominal voltage UN		450 V	

EAC			EAC-Zulassung
-----	-------------------------------------------------------------------------------------	--	---------------

PCB terminal block - MKDSO 2,5/ 2-L BU - 2901505

Approvals

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E60425-19770427
	B	D
mm ² /AWG/kcmil	30-12	30-12
Nominal current I _N	20 A	10 A
Nominal voltage U _N	300 V	300 V