

## Fuse - SI FORM C 20 A DIN 72581 - 0913744

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Flat-type plug-in fuse, type C, color code: yellow, nominal current: 20 A


The figure shows a version of the article

### Why buy this product

- With snap-in foot for secure pre-assembly on the PCB
- Fuse holder for flat-type fuses with a maximum nominal voltage of 32 V



### Key Commercial Data

Packing unit	50 STK
GTIN	 4 017918 104023
GTIN	4017918104023
Weight per Piece (excluding packing)	1.789 g
Custom tariff number	85361050
Country of origin	Germany

### Technical data

#### General

Color	yellow
Flammability rating according to UL 94	V0

#### Dimensions

Width	5 mm
Length	19 mm

#### General

Fuse	C
Nominal current $I_N$	20 A
Nominal voltage $U_N$	24 V

# Fuse - SI FORM C 20 A DIN 72581 - 0913744

## Technical data

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

## Classifications

### eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27142007
eCl@ss 5.1	27142007
eCl@ss 6.0	27142001
eCl@ss 7.0	27142008
eCl@ss 8.0	27142008
eCl@ss 9.0	27142008

### ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC002298
ETIM 4.0	EC002298
ETIM 5.0	EC002298
ETIM 6.0	EC002298

### UNSPSC

UNSPSC 6.01	30211813
UNSPSC 7.0901	39121410
UNSPSC 11	39121412
UNSPSC 12.01	39121412
UNSPSC 13.2	39121622

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

### Approval details

## Fuse - SI FORM C 20 A DIN 72581 - 0913744

### Approvals

EAC



EAC-Zulassung