

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Custom circuit module, consisting of housing, MKDS 3 connection terminal blocks and PCB

Why buy this product

- ☑ Practical and easy-to-wire conductor connections
- Space-saving accommodation of electronic components in finely graded module versions available with 10 to 150 mm pitch
- ☑ User-friendly and safe mounting on DIN rails according to EN 60715
- High degree of flexibility due to the wide choice of versions
- Uniform and appropriate housing technology
- ☑ Inflammability class V0 insulation material (according to UL 94)
- Shock and contamination-proof accommodation of electronic components
- Universal PCBs for all pitches



Key Commercial Data

Packing unit	2 STK
GTIN	4 017918 082727
GTIN	4017918082727
Weight per Piece (excluding packing)	144.000 g
Custom tariff number	85369010
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

General

Housing type	Component housing	
Housing material	Polycarbonate fiber reinforced	
Color (RAL)	green	



Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C 125 °C		
Dimensions			
Length	75 mm		
Constructional height	47.5 mm		
Width	75 mm		

5 mm 75 mm

Technical data

Pitch

Depth

Power dissipation without gap	3.3 W
Power dissipation with 20 mm gap	3.9 W
Number of positions	28

Standards and Regulations


Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50		
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"		

Drawings


Dimensional drawing



Pitch 5 mm

- a = Area for mounting components, 38 mm in the hood
- b = Area for mounting components, 45 mm in the housing

Dimensional drawing



- 1 = Top edge of the PCB
- B = Housing width

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506



Classifications

eCl	@ss
	(ω, ω, ω)

eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031
ETIM 6.0	EC001031

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Α	n	nı	'n	v	al	s
, v	\sim	\sim	•	٧,	u	J

Approvals

EAC / EAC

Ex Approvals

Approval details

EAC EHL	EAC-Zulassung
---------	---------------

EAC EAC B.01742



Accessories

Accessories

Device marking

Marking material - EMG-GKS 22 - 2941594



Device marking label, width: 22 mm, area: 22 x 8 mm, e.g. for EML(20x8) R adhesive marking material

Filler plug

Electronic housing - EMG-KA - 2941510



Terminal block/screw cover, set consisting of 50 strips each for terminal blocks and screw openings, 1 strip covers 12 terminal points.

Marking material - EMG-GKS 12 - 2947035



Device marking label, width: 12 mm, area: 12 x 8 mm, e.g. for EML(10x7) R adhesive marking material

Necessary add-on products

Electronic housing - EMG 75-H 7,5MM KLAR - 2947954



Covering hood, for the contact and dust-protected encapsulation of the components, in transparent design. Height: 7.5 mm, width: 75 mm

Electronic housing - EMG 75-H 15MM KLAR - 2947967



Covering hood, for the contact and dust-protected encapsulation of the components, in transparent design. Height: 15 mm, width: 75 mm



Accessories

Electronic housing - EMG 75-H 52MM GN - 2947970



Covering hood, for the contact and dust-protected encapsulation of the components, in green design. Height: 52 mm, width: 75 mm

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com