

Type 3 surge protection base element - UAK-BE - 2748674

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Base element for accommodating surge protection plugs UAK for single-phase power supply units, for mounting on NS 32 and NS 35/7.5, housing width: 17.5 mm

RoHS

Key Commercial Data

Packing unit	10 STK
GTIN	 4 017918 062583
GTIN	4017918062583
Weight per Piece (excluding packing)	58.600 g
Custom tariff number	85363010
Country of origin	Greece
Note	Made to Order (non-returnable)

Technical data

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C

General

Nominal current I_N	26 A
Mounting type	NS 32/NS 35
Housing material	PA

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801

Type 3 surge protection base element - UAK-BE - 2748674

Classifications

eCl@ss

eCl@ss 5.1	27130801
eCl@ss 6.0	27130803

ETIM

ETIM 2.0	EC000472
ETIM 3.0	EC000472
ETIM 4.0	EC000472
ETIM 5.0	EC000472

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Accessories

Accessories

Coding element

Coding element - CS-UFBK - 2781576



Coding pins for later coding of the base elements without coding belonging to the PLUGTRAB UFBK and UAK product ranges.

Marker pen

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

Terminal marking

Type 3 surge protection base element - UAK-BE - 2748674

Accessories

Zack marker strip - ZB 5,8:UNBEDRUCKT - 2715209



Zack marker strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snap into tall marker groove, for terminal block width: 5.8 mm, lettering field size: 5.75 x 10.5 mm