

# Snap-in markers - UCT-EM (10X8) - 0801485

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Snap-in markers, Sheet, white, unlabeled, can be labeled with: THERMOMARK PRIME, THERMOMARK CARD, BLUEMARK ID, BLUEMARK ID COLOR, BLUEMARK CLED, BLUEMARK LED, TOPMARK NEO, mounting type: snapped into marker carrier, lettering field size: 10 x 8 mm



## Key Commercial Data

|                                      |               |
|--------------------------------------|---------------|
| Packing unit                         | 10 STK        |
| GTIN                                 |               |
| GTIN                                 | 4046356673358 |
| Weight per Piece (excluding packing) | 11.000 g      |
| Custom tariff number                 | 39269097      |
| Country of origin                    | Poland        |

## Technical data

### Dimensions

|            |       |
|------------|-------|
| Length (b) | 8 mm  |
| Width (a)  | 10 mm |

### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C |
|---------------------------------|-------------------|

### General

|   |                                |
|---|--------------------------------|
| Color   | white                          |
| Components  | free from silicone and halogen |
| Flammability rating according to UL 94                              | V0                             |
| Material  | PC                             |
| RoHS compliant  | Yes                            |
| Wipe resistance   | DIN EN 61010-1 (VDE 0411-1)    |
| Number of individual labels   | 36                             |
| Number of individual labels per row                                 | 6                              |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02           |

# Snap-in markers - UCT-EM (10X8) - 0801485

## Technical data

### General

|  |                              |
|--|------------------------------|
| Result   | Test passed                  |
| Test specification weathering-resistance           | Following ISO 4892-2:2013-03 |
| Test duration                                      | 96 h                         |
| Wipe resistance test result                        | Test passed                  |
| Salt spray test specification                      | DIN EN 60068-2-11:2000-02    |
| Test duration                                      | 96 h                         |
| Salt spray testing result                          | Test passed                  |
| Wipe resistance of test specification inscriptions | IEC 61010-1:2010-06          |
| Result   | Test passed                  |
| Marking mounting type                              | snapped into marker carrier  |
| Result   | Test passed                  |
| Oxygen index (DIN EN ISO 4589-2)                   | 32.4 %                       |
| R22  | HL 1 - HL 3                  |
| R23  | HL 1 - HL 3                  |
| R24  | HL 1 - HL 3                  |

### Standards and Regulations

|  |                                     |
|--|-------------------------------------|
| Wipe resistance  | DIN EN 61010-1 (VDE 0411-1)         |
| Flammability rating according to UL 94                 | V0                                  |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3 HL 1 - HL 3 HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3 HL 1 - HL 3 HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3 HL 1 - HL 3 HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26 | HL 1 - HL 3 HL 1 - HL 3 HL 1 - HL 3 |

## Drawings

Pictogram



## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141100 |
| eCl@ss 6.0 | 27149100 |
| eCl@ss 7.0 | 27149129 |
| eCl@ss 8.0 | 27149129 |
| eCl@ss 9.0 | 27400629 |

# Snap-in markers - UCT-EM (10X8) - 0801485

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |
| ETIM 6.0 | EC001288 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39131504 |

## Accessories

### Accessories

#### Magazine

Magazine - THERMOMARK CARD-UCT-MAG12 - 0830399



Magazine for the THERMOMARK CARD printer, for accommodating UCT sheets UCT-EM (10 x 8) and UCT-EM (12 x 7)

Magazine - TMP-UCT-MAG12 - 0803354



Magazine, for the THERMOMARK PRIME and the THERMOMARK CARD, for accommodating UCT-EM (10x8), UCT-EM (12x7)