

Valve connectors - SACC-V-3CON-PG9/A-1L-SV 120V - 1527922

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Valve connectors, 3-position, Valve connector A, with 1 LED, connected with Varistor, Screw connection, cable gland Pg9, external cable diameter 6 mm ... 8 mm



Key Commercial Data

Packing unit	1 STK
GTIN	4 017918 980962
GTIN	4017918980962
Weight per Piece (excluding packing)	25.240 g
Custom tariff number	85366990
Country of origin	Hungary

Technical data

Dimensions

External diameter	6 mm 8 mm
External dameter	5 Hill 5 Hill

Ambient conditions

Ambient temperature (operation)	-25 °C 85 °C (valve plug)
Degree of protection	IP65

General

Rated current at 40°C	10 A
Rated voltage	110 V
Number of positions	3
Color handle area	transparent
Insulation resistance	≥ 100 MΩ



Valve connectors - SACC-V-3CON-PG9/A-1L-SV 120V - 1527922

Technical data

General

Status display	1 LED
Protective circuit/component	Varistor
Overvoltage category	II
Degree of pollution	3
Connection method	Screw connection
Conductor cross section	0.34 mm² 1.5 mm²
Conductor cross section AWG	22 16
Insertion/withdrawal cycles	50 Valve connector

Material

Flammability rating according to UL 94	НВ
Valve plug contact material	CuSn
Valve plug contact surface material	Ni
Valve plug contact insert material	PA6
Material housing valve plug	PA6
Sealing material	NBR

Standards and Regulations


Flammability rating according to UL 94	НВ
--	----


Environmental Product Compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing







Valve connectors - SACC-V-3CON-PG9/A-1L-SV 120V - 1527922

Classifications

eCl@ss

eCl@ss 4.0	27140815
eCl@ss 4.1	27140815
eCl@ss 5.0	27143423
eCl@ss 5.1	27143400
eCl@ss 6.0	27279200
eCl@ss 7.0	27440104
eCl@ss 8.0	27440104
eCl@ss 9.0	27440105

ETIM

ETIM 2.0	EC001121
ETIM 3.0	EC002062
ETIM 4.0	EC002062
ETIM 5.0	EC002062
ETIM 6.0	EC002925

UNSPSC

UNSPSC 6.01	31251501
UNSPSC 7.0901	31251501
UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	32151909

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC [FI

EAC-Zulassung



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com