

## Potential bridge - FBS-PV UT - 3047358

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Vertical potential bridge, to connect the upper and lower level



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 046356 094733
GTIN	4046356094733
Weight per Piece (excluding packing)	1.200 g
Custom tariff number	85366990
Country of origin	Poland

### Technical data

#### Technical data

Color	black
Material	Copper
Number of positions	1
Length	3 mm
Height	44 mm
Width	5.2 mm
Ambient temperature (operation)	125 °C
Flammability rating according to UL 94	V0
Maximum load current	22 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

# Potential bridge - FBS-PV UT - 3047358

## Technical data

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141140
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140
eCl@ss 9.0	27141140

### ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489
ETIM 6.0	EC000489

### UNSPSC

UNSPSC 6.01	30211829
UNSPSC 7.0901	39121426
UNSPSC 11	39121426
UNSPSC 12.01	39121426
UNSPSC 13.2	39121426

## Approvals

### Approvals

---

Approvals

EAC

## Potential bridge - FBS-PV UT - 3047358

### Approvals

---

Ex Approvals

---

### Approval details

EAC		EAC-Zulassung
-----	---	---------------

---