

Accessories - MSTBC-MT 0,2-0,5 - 1879531

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Module socket contact, is inserted into the plug housing MSTBC after crimping the conductor, for conductors from 0.2 to 0.5 mm²

RoHS

Key Commercial Data

Packing unit	100 pc
GTIN	 4 017918 269067
GTIN	4017918269067

Technical data

General

Nominal current	9 A (with 0.5 mm ² conductor cross section)
Conductor cross section flexible min.	0.2 mm ²
Max. conductor cross section, flexible	0.5 mm ²

Connection data

Core diameter including insulation	1.15 mm ... 2.3 mm
Stripping length of individual wires	3 mm

Material data

Contact material	CuFe
Contact surface material	Tin-plated


Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Accessories - MSTBC-MT 0,2-0,5 - 1879531

Dimensional drawing



Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC



B.01742

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>