

Torque screwdriver - TSD 02 SAC - 1208487

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors

The figure shows the TSD 04 SAC version

Your advantages

- $\ensuremath{\,^{\square}\,}$ TSD ... SAC torque screwdrivers with a range of preset torques from 0.2 Nm to 2.5 Nm
- For the TSD-M... torque screwdrivers, the torque can be custom-set

Key Commercial Data

Packing unit	1 pc
GTIN	4 046356 014571
GTIN	4046356014571
Weight per Piece (excluding packing)	93.500 g
Custom tariff number	82054000
Country of origin	Czech Republic

Technical data

Dimensions

Length (b)	205 mm
Width (a)	37 mm
Blade thickness	0 mm
Blade width	0 mm
Blade height	100 mm

General

Color	black
Туре	Hexagonal SW4

Environmental Product Compliance



Torque screwdriver - TSD 02 SAC - 1208487

Technical data

Environmental Product Compliance

California Proposition 65	Further information on California's prop. 65 is available under
	"Downloads" in the manufacturer's declaration

Classifications

eCl@ss

eCl@ss 4.0	21040401
eCl@ss 4.1	21040401
eCl@ss 5.0	21040401
eCl@ss 5.1	21040400
eCl@ss 6.0	21040400
eCl@ss 7.0	21040417
eCl@ss 8.0	21040417
eCl@ss 9.0	21040417

ETIM

ETIM 2.0	EC000158
ETIM 3.0	EC000158
ETIM 4.0	EC000158
ETIM 5.0	EC002132
ETIM 6.0	EC002132

UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details



Torque screwdriver - TSD 02 SAC - 1208487

Approvals

EAC

EHE

RU x-DE.xx08.B.02974

Accessories

Accessories

Screwdriver tools

Tool - SAC BIT M8-D10 - 1208461



Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 10 mm, for 4 mm hexagonal drive

Tool - SACC BIT M8-D12 - 1208474



Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 12 mm, for 4 mm hexagonal drive

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com