

# Torque screwdriver - TSD 08 SAC - 1212597

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Torque screw driver with preset torque of 0.8 Nm, with 4 mm hexagon for accommodating SAC bits, two-component handle with non-slip grip

The figure shows the TSD 04 SAC version

### Your advantages

- For the TSD-M... torque screwdrivers, the torque can be custom-set
- $\ensuremath{\,^{\square}\,}$  TSD ... SAC torque screwdrivers with a range of preset torques from 0.2 Nm to 2.5 Nm

## **Key Commercial Data**

Packing unit	1 pc	
GTIN	4 046356 590716	
GTIN	4046356590716	

## Technical data

## Dimensions

Length (b)	205 mm
Width (a)	37 mm
Blade thickness	0 mm
Blade width	0 mm
Blade height	100 mm

#### General

Color	black
Туре	Hexagonal SW4
Material	alloyed tool steel

### **Environmental Product Compliance**

L.alifornia Proposition no	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration



# Torque screwdriver - TSD 08 SAC - 1212597

Approvals			
Approvals			
Approvals			
EAC			
Ex Approvals			
Approval details			
EAC	EAC		RU x- DE.xx08.B.02974

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com