PHŒNIX CONTACT

Test adapter - PAI-4-FIX-5/6 WH - 3035983

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

Your advantages

☑ Make contact and latch securely to any point in the function shaft

☑ Test adapter for accommodating safety test plugs with a 4 mm diameter

RoHS

Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	4 055626 293660
GTIN	4055626293660
Weight per Piece (excluding packing)	1.380 g
Custom tariff number	85366990
Country of origin	Poland

Technical data

Dimensions

Height	45.3 mm
Length	5.8 mm
Width	5.8 mm
Diameter	5.8 mm
Pin diameter	2.4 mm

General

Note	Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in
	Do not plug in while the power is connected

Test adapter - PAI-4-FIX-5/6 WH - 3035983

Technical data

General

	Latching testing accessories, therefore only suitable for being plugged in once
Color	white

Material	Copper
Ambient temperature (operation)	-40 °C ... 125 °C
Max. voltage	250 V
Maximum load current	10 A
Insertion/withdrawal cycles	1

Standards and Regulations

Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 4.0	27141127
eCl@ss 4.1	27141127
eCl@ss 5.0	27141127
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27440313
eCl@ss 8.0	27440313
eCl@ss 9.0	27440313

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002255
ETIM 5.0	EC002255
ETIM 6.0	EC002255

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121410

Test adapter - PAI-4-FIX-5/6 WH - 3035983

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC	EHC	EAC-Zulassung