

Network cable - VS-OE-OE-936-100,0 - 1416570


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Network cable, PROFINET CAT5 (100 Mbps), 4-position, PE-X halogen-free, black RAL 9005, shielded, free cable end, on free cable end, cable length: 100 m, For railway applications



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 479264
GTIN	4046356479264
Weight per Piece (excluding packing)	7,527.000 g
Custom tariff number	85444290
Country of origin	Germany

Technical data

Dimensions

Length of cable	100 m
-----------------	-------

General data

Number of positions	4
Signal type/category	PROFINET CAT5 (IEC 11801:2002), 100 Mbps

Cable

Cable type	PROFINET railway applications
Cable type (abbreviation)	936
Signal type/category	PROFINET CAT5 (IEC 11801), 100 Mbps
Cable structure	1x4xAWG22/7; SF/TQ
Conductor cross section	4x 0.34 mm ²
AWG signal line	22
Conductor structure signal line	7x 0.25 mm
Core diameter including insulation	1.95 mm
Wire colors	white-blue, orange-yellow

Network cable - VS-OE-OE-936-100,0 - 1416570

Technical data

Cable

Overall twist	Star quad
Shielding	Plastic-coated aluminum foil, tinned copper braided shield
Optical shield covering	100 %
External sheath, color	black RAL 9005
Outer sheath thickness	≥ 0.8 mm
External cable diameter D	7.25 mm ±0,3 mm
Minimum bending radius, fixed installation	6 x D
Minimum bending radius, flexible installation	10 x D
Cable weight	81 g/m
Outer sheath, material	PE-X
Material conductor insulation	PE-X
Conductor material	silver-plated Cu litz wires
Conductor resistance	≤ 54.4 Ω/km
Working capacitance	≤ 65 pF (core-core)
	≤ 100 pF (core-shield)
Wave impedance	100 Ω ±5 Ω (f = 100 MHz)
Near end crosstalk attenuation (NEXT)	80 dB (with 1 MHz)
	76 dB (at 4 MHz)
	67 dB (at 10 MHz)
	60 dB (at 31.5 MHz)
	56 dB (at 62.5 MHz)
	53 dB (at 100 MHz)
Remote crosstalk attenuation (FEXT)	80 dB (with 1 MHz)
	70 dB (at 4 MHz)
	65 dB (at 10 MHz)
	58 dB (at 31.5 MHz)
	59 dB (at 62.5 MHz)
	67 dB (at 100 MHz)
Attenuation	2 dB (with 1 MHz)
	4 dB (at 4 MHz)
	6.5 dB (at 10 MHz)
	10.5 dB (at 31.5 MHz)
	14 dB (at 62.5 MHz)
	18 dB (at 100 MHz)
Return loss (RL)	35 dB (at 4 MHz)
	35 dB (at 10 MHz)
	35 dB (at 31.5 MHz)
	33 dB (at 62.5 MHz)
	33 dB (at 100 MHz)
Signal speed	66 c

Network cable - VS-OE-OE-936-100,0 - 1416570

Technical data

Cable

Shield attenuation	40 dB (30 MHz ≤ f ≤ 100 MHz)	
Coupling resistance	200.00 mΩ/m (f ≤ 30 MHz)	
Nominal voltage, cable	300 V AC	
Test voltage, cable	2000 V AC (50 Hz, 5 minutes)	
Fire protection in rail vehicles	BS 6853 (Category Ia, Ib, II)	
	GM/RT 2130 (Category Ia, Ib, II)	
	EN 45545 (Risk level HL1 - HL3)	
	DIN 5510 (Fire protection level 1, 2, 3, 4)	
	NF F16-101 (Category A1, A2, B)	
	NF F16-101 (Class C/F0)	
	NFPA 130	
	UNI CEI 11170 (Risk level LR1 - LR4)	
	Flame resistance	EN 60332-1-2
		EN 50266
	EN 60332-3-25	
	NF C32-070, 2.1	
	NF C32-070, 2.2	
	UL 1685, 12 (FT4)	
	in accordance with ISO 6722-1 5.22 (UN ECE-R 118.01)	
Halogen-free	According to EN 50267-2-1	
Resistance to oil	according to IRM 902, 72 h at 100 °C	
Other resistance	Resistance to fuels according to IRM 903, 168 h at 70 °C	
Concentration of fumes	BS 6853 D.8.7	
	EN 61034-2	
	UL 1685, 12 (FT4)	
Fume corrosiveness	EN 50267-2-2	
Fume toxicity	BS 6853 B.1	
	EN 50305, 9.2	
Ambient temperature (operation)	-50 °C ... 90 °C (cable, fixed installation)	
	-40 °C ... 90 °C (cable, flexible installation)	


Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Network cable - VS-OE-OE-936-100,0 - 1416570

Cable cross section



PROFINET railway applications [936]

Classifications

eCl@ss

eCl@ss 4.0	27060307
eCl@ss 4.1	27060307
eCl@ss 5.0	27060307
eCl@ss 5.1	19030300
eCl@ss 6.0	27061800
eCl@ss 7.0	27061801
eCl@ss 8.0	27061801
eCl@ss 9.0	27061801

ETIM

ETIM 3.0	EC000830
ETIM 4.0	EC000830
ETIM 5.0	EC000830
ETIM 6.0	EC000830

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	26121604

Approvals

Approvals

Approvals


EAC

Ex Approvals

Network cable - VS-OE-OE-936-100,0 - 1416570

Approvals

Approval details

EAC		RU C- DE.AI30.B.00767
-----	---	--------------------------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>