PHŒNIX CONTACT

Housing - HC-STA-D50-BWD-ELC-AL - 1424412

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Panel mounting base D50, with double locking latch, material: Die-cast aluminum, salt water resistant, height: 32 mm, cable gland: none, support sleeve: no, Standard, with flat gasket

Your advantages

☑ good shielding in the event of electromagnetic interference

RoHS   (((EMC ready)))

Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4055626371528
Weight per Piece (excluding packing)	105.000 g
Custom tariff number	85389099
Country of origin	China

Technical data

Dimensions

Height	32 mm
Width	65 mm
Length	102 mm
Length of the assembly cutout	73 mm
Width of the assembly cutout	48 mm

Ambient conditions

Degree of protection of housing (IP)	IP66
	IP67
Ambient temperature (operation)	-40 °C ... 125 °C

General

# Housing - HC-STA-D50-BWD-ELC-AL - 1424412

Technical data

General

Size	D50
Housing type	Panel mounting base
Color	gray aluminum
Locking type	with double locking latch
Screw connection	none
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Seal material	NBR, conductive
Material lock	PA

### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing

Dimensional drawing

Dimensional drawing

Mounting cutout

Classifications

eCl@ss

eCl@ss 5.1	27261200
eCl@ss 6.0	27261200
eCl@ss 7.0	27440202
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

ETIM

ETIM 5.0	EC000437
ETIM 6.0	EC000437

Approvals

Approvals

Housing - HC-STA-D50-BWD-ELC-AL - 1424412

Approvals

Approvals

GL / EAC

Ex Approvals

Approval details

GL	GL	http://exchange.dnv.com/tari/	6196614 HH

EAC	EAC		EAC-Zulassung