

Crimping pliers - CRIMPFOX 6H CUS - 1212768

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Crimping pliers, laser marked according to customer specifications, for ferrules according to DIN 46228, 0.14 - 6 mm², unlockable pressure lock, lateral entry

The figure shows CRIMPFOX 10S CUS

Your advantages

- These compact crimping pliers have been designed to reduce effort when working
- The way in which the handles and the die are arranged means that the ferrules can be fitted however the tool is held





Key Commercial Data

Packing unit	1 pc
GTIN	4 046356 942959
GTIN	4046356942959
Weight per Piece (excluding packing)	445.800 g
Custom tariff number	82032000
Country of origin	Germany

Technical data

Dimensions

Length (b)	175 mm
General	
Compression	HEX crimp
Type of contact	Ferrules
Weight	380 g
Min. cross section	0.14 mm²
Max. cross section	6 mm²
AWG min	25



Crimping pliers - CRIMPFOX 6H CUS - 1212768

Technical data

\sim			
(J	eı	ıe	ra

AWG max	10

Environmental Product Compliance

California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration

Classifications

eCl@ss

eCl@ss 5.1	21040300
eCl@ss 6.0	21049000
eCl@ss 7.0	21049090
eCl@ss 8.0	21049090
eCl@ss 9.0	21043811

ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186
ETIM 5.0	EC000168
ETIM 6.0	EC000168

UNSPSC

UNSPSC 13.2	27111518

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC RU x-DE.xx08.B.02974



Crimping pliers - CRIMPFOX 6H CUS - 1212768

Accessories

Accessories

Mounting material

Replacement spring - CRIMPFOX/SPR-2 - 1212047



Spare recuperating spring

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com