

Protective covers - HC-B10-BCSFS-P-BK - 1414625


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Protective cover B10, for single locking latch, protective cover material: PA, height: 18.5 mm, seal: no, diameter of retaining cord eyelet: 40 mm



Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 055626 030661
GTIN	4055626030661
Weight per Piece (excluding packing)	21.000 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

Dimensions

Length	76 mm
Width	46 mm
Height	18.5 mm
Diameter of retaining cord eyelet	40 mm

Ambient conditions

Degree of protection	IP66
Ambient temperature (operation)	-20 °C ... 100 °C

General

Size	B10
Material	PA
Flammability rating according to UL 94	HB
Color	black
Seal present	no

Protective covers - HC-B10-BCSFS-P-BK - 1414625

Technical data

General

Note	Protective cover for supporting base element with single locking latch
Connection	Plastic protective cover for short-term protection

Standards and Regulations


Flammability rating according to UL 94	HB
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Dimensional drawing

Classifications

eCl@ss

eCl@ss 5.1	23110100
eCl@ss 6.0	27261200
eCl@ss 7.0	27440208
eCl@ss 8.0	27440208
eCl@ss 9.0	27440208

ETIM

ETIM 5.0	EC002314
ETIM 6.0	EC002314

UNSPSC

UNSPSC 13.2	39121421
-------------	----------

Approvals

Approvals

Protective covers - HC-B10-BCSFS-P-BK - 1414625


Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.AI30.B.01102
-----	---	--------------------------
