

Crimp contact - SM-36KP005 - 1605749

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Crimp contact, turned, Single contact, contact diameter: 3.6 mm, crimp range: 1 mm² ... 2.5 mm²

The figure may differ depending on the connection area

Your advantages

- ☑ Crimping connection: vibration- and temperature-resistant assembly
- High tensile strength of the connection



Key Commercial Data

Packing unit	20 pc	
Minimum order quantity	20 pc	
GTIN	4 046356 254595	
GTIN	4046356254595	
Weight per Piece (excluding packing)	5.810 g	
Custom tariff number	85366990	
Country of origin	Germany	

Technical data

General

Contact type	turned	
Contact diameter	3.6 mm	
Type of contact	Pin	
Connection method	Crimp connection	
Insertion/withdrawal cycles mechanical	100	
Litz wire cross section min.	1 mm²	
Litz wire cross section max.	2.5 mm²	



Crimp contact - SM-36KP005 - 1605749

Technical data

General


Contact material	CuZn	
Contact surface	Nickel-plated (Ni), with gold coating (Au)	

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1	
China RoHS	Environmentally Friendly Use Period = 50	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27261200
eCl@ss 6.0	27261200
eCl@ss 7.0	27440204
eCl@ss 8.0	27440204
eCl@ss 9.0	27440204

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC000796
ETIM 5.0	EC000796
ETIM 6.0	EC000796

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404



Crimp contact - SM-36KP005 - 1605749

Classifications

UNSPS)
--------------	---

UNSPSC 13.2		39121522	
Approvals			
Approvals			
Approvals			
EAC			
Ex Approvals			
Approval details			
EAC	ERC		B.01742

Accessories

Accessories

Crimping tool

Crimping pliers with digital display - SF-Z0025 - 1607452



Crimping pliers for turned crimp contacts \emptyset 1.0 mm / \emptyset 1.6 mm / \emptyset 2 mm / \emptyset 3.6 mm, litz wire cross section of 0.08 mm² ... 6 mm²

Crimping pliers with digital display - SF-Z0026 - 1607454



Crimping pliers for turned crimp contacts Ø 2 mm / Ø 3.6 mm, litz wire cross section of 1.5 mm $^2 \dots$ 10 mm 2

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com