

Protective covers - HC-B 16-SD-FQU/FS-AL - 1644591

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Protective cover B16, for double locking latch, protective cover material: Al, height: 16 mm, seal: no, With lanyard, diameter of retaining cord eyelet: 30 mm

Key Commercial Data

Packing unit	10 pc
GTIN	
GTIN	4017918904913
Weight per Piece (excluding packing)	70.600 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

Dimensions

Length	94 mm
Width	43.2 mm
Height	16 mm
Diameter of retaining cord eyelet	30 mm

Ambient conditions

Degree of protection	IP66
Ambient temperature (operation)	-40 °C ... 125 °C

General

Size	B16
Type	For supporting base element with double locking latch
Material	Aluminum, die-cast
Color	gray
Seal present	no
Assembly instructions	Not for HC-B...EMC housings

Protective covers - HC-B 16-SD-FQU/FS-AL - 1644591

Technical data

General


Connection	The guide pins of the protective cover must be removed when using coding sockets, pins, and bolts.
------------	--

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Dimensional drawing

Classifications

eCl@ss

eCl@ss 4.0	27141210
eCl@ss 4.1	27141210
eCl@ss 5.0	27149110
eCl@ss 5.1	27149100
eCl@ss 6.0	27261200
eCl@ss 7.0	27440208
eCl@ss 8.0	27440208
eCl@ss 9.0	27440208

ETIM

ETIM 2.0	EC000241
ETIM 3.0	EC002040
ETIM 4.0	EC002314
ETIM 5.0	EC002314
ETIM 6.0	EC002314

UNSPSC

UNSPSC 6.01	30212113
UNSPSC 7.0901	39121712
UNSPSC 11	39121712

Protective covers - HC-B 16-SD-FQU/FS-AL - 1644591

Classifications

UNSPSC

UNSPSC 12.01	39121712
UNSPSC 13.2	39121421

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.AI30.B.01102
-----	---	--------------------------
