

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Sleeve housing, for double locking latch, height 80 mm, without screw connection, 1x Pg29, lateral cable entry



## **Key Commercial Data**

| Packing unit                         | 10 pc           |
|--------------------------------------|-----------------|
| GTIN                                 | 4 017918 149857 |
| GTIN                                 | 4017918149857   |
| Weight per Piece (excluding packing) | 438.090 g       |
| Custom tariff number                 | 85389099        |
| Country of origin                    | Germany         |

### Technical data

#### **Dimensions**

| Height | 80 mm |
|--------|-------|
| Width  | 79 mm |
| Length | 94 mm |

#### Ambient conditions

| Degree of protection of housing (IP) | IP65          |
|--------------------------------------|---------------|
| Ambient temperature (operation)      | -40 °C 125 °C |

#### General

| Note                 | For contact inserts HC-B32, DD144, M |
|----------------------|--------------------------------------|
| Size                 | B32                                  |
| Housing type         | Sleeve housing                       |
| Color                | gray                                 |
| Locking type         | for double locking latch             |
| No. of cable outlets | 1                                    |
| Cable outlet         | lateral                              |

12/27/2018 Page 1 / 4



## Technical data

### General


| Screw connection             | none                |
|------------------------------|---------------------|
| Type of the screw connection | 1x Pg29             |
| Housing material             | Aluminum die-cast   |
| Housing surface material     | Powder-coated, gray |


### **Environmental Product Compliance**

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
|            | No hazardous substances above threshold values          |

## Drawings

#### Dimensional drawing





Dimensional drawing

## Classifications

### eCl@ss

| eCl@ss 4.0 | 27140816 |
|------------|----------|
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27261200 |
| eCl@ss 6.0 | 27261200 |
| eCl@ss 7.0 | 27440202 |
| eCl@ss 8.0 | 27440202 |
| eCl@ss 9.0 | 27440202 |

### **ETIM**

| ETIM 2.0 | EC000437 |
|----------|----------|
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |
| ETIM 6.0 | EC000437 |

## UNSPSC

| UNSPSC 6.01 | 31261502 |
|-------------|----------|



### Classifications

#### **UNSPSC**

| UNSPSC 7.0901 | 31261502 |
|---------------|----------|
| UNSPSC 11     | 31261502 |
| UNSPSC 12.01  | 31261502 |
| UNSPSC 13.2   | 31261501 |

## Approvals

Approvals

Approvals

EAC

Ex Approvals

#### Approval details

EAC

EHE

RU C-DE.Al30.B.01102

#### Accessories

#### Accessories

Full screw connection

Cable gland - G-INS-PG29-M68N-PNES-GY - 1411146



Cable gland, cable gland material: PA, external cable diameter 18 mm ... 25 mm, shielding: no, connecting thread: Pg29, color: silver-gray RAL 7001

#### Cable gland - G-INS-PG29-M68N-NNES-S - 1411176



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 18 mm  $\dots$  25 mm, shielding: no, connecting thread: Pg29, color: silver, with O-ring



### Accessories

Cable gland - G-INSEC-PG29-M68N-NNES-S - 1411201



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 18 mm ... 25 mm, shielding: yes, connecting thread: Pg29, color: silver, with O-ring

Plug for cable screw gland

Screw plug - HC-BS-PG29 - 1674532



Screw plug, Brass, nickel-plated, connecting thread: Pg29, color: silver

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com