


DIN rail bus connectors - ME 22,5 TBUS 1,5/5-ST-3,81BUGY - 2200413

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

DIN rail connector, number of positions: 5, pitch: 3.81 mm



Key Commercial Data

Packing unit	1
GTIN	 4 055626 247434
GTIN	4055626247434
Custom tariff number	85366990

Technical data

General

Housing material	Polyamide
------------------	-----------

Dimensions

Height	20 mm
Width	22.5 mm
Pitch	3.81 mm

Technical data

Number of positions	5
---------------------	---

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702
eCl@ss 8.0	27440309

DIN rail bus connectors - ME 22,5 TBUS 1,5/5-ST-3,81BUGY - 2200413

Classifications

eCl@ss

eCl@ss 9.0	27440309
------------	----------

ETIM

ETIM 5.0	EC002638
ETIM 6.0	EC001031

UNSPSC

UNSPSC 13.2	31261501
-------------	----------

Approvals


Approvals


Approvals


UL Recognized / cUL Recognized / EAC / cULus Recognized


Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E118976-20151204
Nominal voltage UN	150 V	
Nominal current IN	8 A	

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E118976-20151204
Nominal voltage UN	150 V	
Nominal current IN	6 A	

EAC		B.01742
-----	---	---------

cULus Recognized	
------------------	---

