

Sample set - SAMPLE MC 0,5/ 8-G-2,54 P20THR - 1836007

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB headers, nominal current: 6 A, rated voltage (III/2): 160 V, number of positions: 8, pitch: 2.54 mm, color: black, contact surface: Gold, mounting: THR soldering



The figure shows the 10-position version

Your advantages

- ✓ Designed for integration into the SMT soldering process
- ✓ Additional solder anchors reduce the mechanical strain on the soldering spots
- ✓ Gold-plated contacts ensure transfer quality remains stable over the long term
- ✓ Supplied in tape-on-reel packing according to IEC 60286-3 for automated mounting



Key Commercial Data

| | |
|--------------------------------------|--|
| Packing unit | 5 pc |
| Minimum order quantity | 5 pc |
| GTIN |  |
| GTIN | 4055626016948 |
| Weight per Piece (excluding packing) | 1.680 g |
| Custom tariff number | 85366930 |
| Country of origin | Poland |

Technical data

Dimensions

| | |
|--------------|----------|
| Length [l] | 7.1 mm |
| Width | 24.86 mm |
| Pitch | 2.54 mm |
| Dimension a | 17.78 mm |
| Width [w] | 24.86 mm |
| Height [h] | 6.8 mm |
| Height | 4.85 mm |

Sample set - SAMPLE MC 0,5/ 8-G-2,54 P20THR - 1836007

Technical data

Dimensions

| | |
|--------------------------|----------------|
| Length of the solder pin | 2 mm |
| Pin dimensions | 0.64 x 0.64 mm |
| Length | 7.1 mm |

General

| | |
|--|------------------|
| Range of articles | MC 0,5/...-G-THR |
| Insulating material group | IIIa |
| Rated surge voltage (III/3) | 2.5 kV |
| Rated surge voltage (III/2) | 2.5 kV |
| Rated surge voltage (II/2) | 2.5 kV |
| Rated voltage (III/3) | 32 V |
| Rated voltage (III/2) | 160 V |
| Rated voltage (II/2) | 160 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I_N | 6 A |
| Insulating material | LCP |
| Flammability rating according to UL 94 | V0 |
| Color | black |
| Number of positions | 8 |

Standards and Regulations


| | |
|--|--------|
| Connection in acc. with standard | EN-VDE |
| Flammability rating according to UL 94 | V0 |

Environmental Product Compliance


| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Drawings

Drilling diagram



Dimensional drawing



Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27260700 |
|------------|----------|

Sample set - SAMPLE MC 0,5/ 8-G-2,54 P20THR - 1836007

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 6.0 | 27260700 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |
| eCl@ss 9.0 | 27440402 |

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC002637 |
| ETIM 6.0 | EC002637 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 39121409 |
|-------------|----------|

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|---------|
| EAC |  | B.01742 |
|-----|---|---------|