

## Sample set - SAMPLE MC 0,5/ 8-G-2,54 SMD - 1847957

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB headers, nominal current: 6 A, rated voltage (III/2): 160 V, number of positions: 8, pitch: 2.54 mm, color: black, contact surface: Gold, mounting: SMD soldering



The figure shows the 10-position version

### Your advantages

- ✓ Designed for integration into the SMT soldering process
- ✓ Additional solder anchors reduce the mechanical strain on the soldering spots
- ✓ Gold-plated contacts ensure transfer quality remains stable over the long term
- ✓ Supplied in tape-on-reel packing according to IEC 60286-3 for automated mounting



### Key Commercial Data

|                      |                                                                                                         |
|----------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit         | 1                                                                                                       |
| GTIN                 | <br>4 055626 027357 |
| GTIN                 | 4055626027357                                                                                           |
| Custom tariff number | 85366930                                                                                                |

### Technical data

#### Dimensions

|                          |                |
|--------------------------|----------------|
| Length [ l ]             | 7.1 mm         |
| Width                    | 24.9 mm        |
| Pitch                    | 2.54 mm        |
| Dimension a              | 17.78 mm       |
| Width [ w ]              | 24.9 mm        |
| Height [ h ]             | 4.85 mm        |
| Height                   | 4.85 mm        |
| Length of the solder pin | 2 mm           |
| Pin dimensions           | 0.64 x 0.64 mm |
| Length                   | 7.1 mm         |

## Sample set - SAMPLE MC 0,5/ 8-G-2,54 SMD - 1847957

### Technical data

#### General

|                                        |                  |
|----------------------------------------|------------------|
| Range of articles                      | MC 0,5/...-G-SMD |
| Insulating material group              | IIIa             |
| Rated surge voltage (III/3)            | 2.5 kV           |
| Rated surge voltage (III/2)            | 2.5 kV           |
| Rated surge voltage (II/2)             | 2.5 kV           |
| Rated voltage (III/3)                  | 32 V             |
| Rated voltage (III/2)                  | 160 V            |
| Rated voltage (II/2)                   | 160 V            |
| Connection in acc. with standard       | EN-VDE           |
| Nominal current $I_N$                  | 6 A              |
| Insulating material                    | LCP              |
| Flammability rating according to UL 94 | V0               |
| Color                                  | black            |
| Number of positions                    | 8                |

#### Standards and Regulations


|                                        |        |
|----------------------------------------|--------|
| Connection in acc. with standard       | EN-VDE |
| Flammability rating according to UL 94 | V0     |

#### Environmental Product Compliance


|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Drawings

Drilling diagram



Dimensional drawing



### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27260700 |
| eCl@ss 6.0 | 27260700 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |
| eCl@ss 9.0 | 27440402 |

## Sample set - SAMPLE MC 0,5/ 8-G-2,54 SMD - 1847957

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC002637 |
| ETIM 6.0 | EC002637 |

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 13.2 | 39121409 |
|-------------|----------|