

## Sample set - SAMPLE DMC 0,5/ 6-G1-2,54 THR - 1859534

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB headers, nominal current: 6 A, rated voltage (III/2): 160 V, number of positions: 6, pitch: 2.54 mm, color: black, contact surface: Gold, mounting: THR soldering




The figure shows a 10-pos. version with 20 contacts

### Your advantages

- ✓ Gold-plated contacts ensure transfer quality remains stable over the long term
- ✓ Designed for integration into the SMT soldering process
- ✓ Conductor connection on several levels enables higher contact density
- ✓ Small component size for applications where space is at a premium
- ✓ Supplied in tape-on-reel packing according to IEC 60286-3 for automated mounting



### Key Commercial Data

|                      |   |
|----------------------|---|
| Packing unit         | 1   |
| GTIN                 | <br>4 055626 111933 |
| GTIN                 | 4055626111933   |
| Custom tariff number | 85366930  |

### Technical data

#### Dimensions

|                          |                |
|--------------------------|----------------|
| Length [ l ]             | 9.64 mm        |
| Width                    | 15.74 mm       |
| Pitch                    | 2.54 mm        |
| Dimension a              | 12.7 mm        |
| Width [ w ]              | 15.74 mm       |
| Height [ h ]             | 7.39 mm        |
| Length of the solder pin | 2 mm           |
| Pin dimensions           | 0.64 x 0.64 mm |
| Pin spacing              | 2.54 mm        |

## Sample set - SAMPLE DMC 0,5/ 6-G1-2,54 THR - 1859534

### Technical data

#### Dimensions

|        |         |
|--------|---------|
| Length | 9.64 mm |
|--------|---------|

#### General

|  |                    |
|--|--------------------|
| Range of articles                      | DMC 0,5/...-G1-THR |
| Insulating material group              | IIIa               |
| Rated surge voltage (III/3)            | 2.5 kV             |
| Rated surge voltage (III/2)            | 2.5 kV             |
| Rated surge voltage (II/2)             | 2.5 kV             |
| Rated voltage (III/3)                  | 32 V               |
| Rated voltage (III/2)                  | 160 V              |
| Rated voltage (II/2)                   | 160 V              |
| Connection in acc. with standard       | EN-VDE             |
| Nominal current $I_N$                  | 6 A                |
| Insulating material                    | LCP                |
| Flammability rating according to UL 94 | V0                 |
| Color                                  | black              |
| Number of positions                    | 6                  |

#### Standards and Regulations


|  |        |
|--|--------|
| Connection in acc. with standard       | EN-VDE |
| Flammability rating according to UL 94 | V0     |

#### Environmental Product Compliance


|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Drawings

Drilling diagram



Dimensional drawing



### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27260700 |
|------------|----------|

## Sample set - SAMPLE DMC 0,5/ 6-G1-2,54 THR - 1859534

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 6.0 | 27260700 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |
| eCl@ss 9.0 | 27440402 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC002637 |
| ETIM 6.0 | EC002637 |

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 13.2 | 39121409 |
|-------------|----------|

### Approvals

#### Approvals

#### Approvals

#### EAC

#### Ex Approvals

### Approval details

|     |   |         |
|-----|---|---------|
| EAC |  | B.01742 |
|-----|---|---------|

### Accessories

#### Accessories

#### Labeled terminal marker

Marker card - SK 2,54/2,8:FORTL.ZAHLEN - 0804853




Marker card, Card, white, labeled, Horizontal: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 99, mounting type: adhesive, for terminal block width: 2.54 mm, lettering field size: 2.54 x 2.8 mm

### Additional products

## Sample set - SAMPLE DMC 0,5/ 6-G1-2,54 THR - 1859534

### Accessories

Printed-circuit board connector - DFMC 0,5/ 6-ST-2,54 - 1844617



Plug, nominal current: 6 A, rated voltage (III/2): 160 V, number of positions: 6 with 12 contacts, pitch: 2.54 mm, connection method: spring connection, color: black, contact surface: gold