

Power cable - PLD E 608-CA-3.0/FS AM - 2702302

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Power cable, 3-position, PVC, orange RAL 2004, free cable end, on Socket straight, black, cable length: 3 m

Product Description

The cable serves to connect 600 class PLD enclosure lights to the supply voltage.



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 112275
GTIN	4055626112275
Weight per Piece (excluding packing)	315.700 g
Custom tariff number	85444290
Country of origin	Germany

Technical data

Dimensions

Length of cable	3 m
Stripping length of the free conductor end	32 mm (Protective conductor (PE) 39 mm)

Ambient conditions

Degree of protection	IP20
	IP40 (plugged in)

General

Rated current at 40°C	16 A
Rated voltage	250 V AC
Number of positions	3
Coding	black
Insertion/withdrawal cycles	100

Power cable - PLD E 608-CA-3.0/FS AM - 2702302

Technical data

Material

Material, knurls	not available
------------------	---------------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 5.1	27049000
eCl@ss 6.0	27279200
eCl@ss 7.0	27279218
eCl@ss 8.0	27279218
eCl@ss 9.0	27060311

ETIM

ETIM 5.0	EC002556
ETIM 6.0	EC001855

UNSPSC

UNSPSC 13.2	31251501
-------------	----------

Accessories

Accessories

Installation connector

Connector - PLD E 608-CO-MS - 2702308



Connector for series connection, black, 3-pos.

Power distributor

T distributor - PLD E 608-CO-MS/FS/FR - 2702310



T-distributor with 2 sockets and one connector for series connection, black, 3-pos.

