

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



RJ45 sleeve housings, degree of protection: IP67, number of positions: 8, material: PA, cable outlet: straight, color: jet black RAL 9005

Your advantages

- ${\ensuremath{\,^{\scriptsize \Box}}}$ High-quality and inexpensive solution in the IP protection zone
- Simple operation
- IP65/67

RoHS

Ethernet

Key Commercial Data

Packing unit	5 pc
Minimum order quantity	5 рс
GTIN	4 046356 163170
GTIN	4046356163170
Weight per Piece (excluding packing)	14.400 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Mechanical characteristics

Number of positions	8
Insertion/withdrawal cycles	≥ 1000
External cable diameter	5 mm 8.5 mm
Cable outlet	straight
Color	jet black RAL 9005
Degree of protection	IP67
Туре	RJ45, IP67, version 6
No. of cable outlets	1

Ambient conditions




Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C 80 °C
Material data	
Flammability rating according to UL 94	V0
Housing material	PA
O-ring material	FPM
Cable seal material	NBR
Material housing intermediate seal	NBR
Electrical characteristics	
Number of positions	8
Overvoltage category	
Degree of pollution	2
Rated voltage (III/3)	72 V (DC)
Standards and Regulations	
Flammability rating according to UL 94	V0
Environmental Product Compliance	
China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



RJ45 sleeve housing IP67

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27261200
eCl@ss 6.0	27261200
eCl@ss 7.0	27440202
eCl@ss 8.0	27440202



Classifications

eCl@ss

	eCl@ss 9.0	27440202
--	------------	----------

ETIM

ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437
ETIM 6.0	EC000437

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC	EAC		B.01742
-----	-----	--	---------

Accessories

Accessories

Male insert

RJ45 male insert - VS-08-ST-H11-RJ45 - 1652716



RJ45 pin insert, CAT5, 8-pos., shielded, IDC connection technology, for 27 ... 26 AWG litz wires, with strain relief



Accessories

RJ45 male insert - VS-08-ST-H21-RJ45 - 1652729



RJ45 male insert, CAT6, 8-pos., shielded, IDC displacement connection, for litz wire AWG 25 ... 24 and solid wires AWG 24, with strain relief

RJ45 male insert - VS-08-RJ45-10G/C - 1418853



Male insert RJ45, CAT6_A, 10 Gigabit

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com