

Marker for terminal blocks - ZB 6,LGS:(1-100/VERP.) - 1051919

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Marker for terminal blocks, Strip, white, labeled, printed horizontally: Consecutive numbers, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 10.5 x 6.15 mm

The figure shows the version ZB 6:UNBEDRUCKT



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 255725 |
| GTIN | 4017918255725 |

Technical data

Dimensions

| | |
|-----------|------|
| Width (a) | 6 mm |
|-----------|------|

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 100 °C |
|---------------------------------|-------------------|

General

| | |
|--|--------------------------------|
| Color | white |
| Type | high |
| Components | free from silicone and halogen |
| Flammability rating according to UL 94 | V2 |
| Material | PA |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Printing direction | printed horizontally |
| Printing | Consecutive numbers |
| Number of individual labels | 10 |
| Number of individual labels per row | 10 |
| Number of marker strips | 10 |

Marker for terminal blocks - ZB 6,LGS:(1-100/VERP.) - 1051919

Technical data

General

| | |
|-----------------------|------------------------------|
| Marking mounting type | snap into tall marker groove |
|-----------------------|------------------------------|

Standards and Regulations

| | |
|--|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Flammability rating according to UL 94 | V2 |

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>