

Fiber optic contact insert - VC-FSMA-M-2 SET - 1855432

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Quick mounting plug for polymer fiber cable, for the contact carrier module VC-AFOS 2, length: 27 mm, width: 7 mm, 2 pcs. each as set

Your advantages

- Clear representation
- For a variety of applications



Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4017918162696

Technical data

Mechanical characteristics

Number of positions	1
Connection profile	F-SMA type 905, IEC 874-2
Fiber type	Polymer fiber
Insertion/withdrawal cycles	> 100
Tightening torque, min.	0.1 Nm
Tightening torque max.	0.2 Nm
Degree of protection	IP20
Type	FSMA

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
---------------------------------	------------------

Material data

Housing material	Nickel silver
Contact material	Nickel silver

Fiber optic contact insert - VC-FSMA-M-2 SET - 1855432

Technical data

Material data

Cable gland material	CuZn
Height	7 mm

Optical characteristics


Attenuation	< 3 dB
-------------	--------

Environmental Product Compliance

	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing



Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	--	---------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>